



SPECIAL LNB-MOUNT

- || Rail system with additional feed adaptors Ø 40 mm for simultaneous reception of up to 4 satellites:
Min. angle distances:
SAT 75 / SAT 85: 6°
SAT 100: 4°
SAT 120: 3°
- || Easy mounting on all DELTA Electronics reflectors



MFH 2



MFH 4

Type	MFH 2	MFH 3	MFH 4
Description	Multifeed mount	Multifeed mount	Multifeed mount
Item No.	57001191	57001192	57001193
LNB fittings	2	3	4
Provided LNB fittings	1	2	3
Shift range	6	25	25
Weight	0.2 kg	0.4	0.5

LNB'S

- || Low Noise Block Converter for conversion of TV SAT transponders into the SAT-IF range (L-Band)
- || Waterproof die-cast housing and additional protection by outer plastic housing
- || Suitable for all standard feed mounts of 40 mm Ø
- || Low power consumption
- || Low noise and low distortion



Type	UC 21	UC 44	UC 44 S
Description	Single-LNB	Quattro-LNB	Quad-LNB
Item No.	57000881	57000885	57000886
Frequency range low-band	10.70 - 11.70 GHz	10.70 - 11.70 GHz	10.70 - 11.70 GHz
high-band	11.70 - 12.75 GHz	11.70 - 12.75 GHz	11.70 - 12.75 GHz
Gain	> 50 dB	> 50 dB	> 50 dB
Oscillator frequency	9.75 low 10.60 high	9.75 low 10.60 high	9.75 low 10.60 high
Polarization decoupling	25 dB	25 dB	25 dB
Switching voltage (H/V)	14 / 18 VDC	12...18 VDC	4 x 14 / 18 VDC
Band switching signals	0 / 22 kHz	–	4 x 0 / 22 kHz
Current consumption	130 mA	220 mA	220 mA
DC Input	12 - 20 V	12 - 20 V	12 - 20 V
Feed fitting	40 mm	40 mm	40 mm
Operating temperature	-40...+60 °C	-40...+60 °C	-40...+60 °C
Weight	0.38 kg	0.47 kg	0.47 kg