

OPTICAL ACCESSORIES

- || **Optical attenuator:** Ensures that the optical attenuation from the output of the LNB to the input of the converter is maintained min 9 dB FC/PC (male-female connector)
- || **Optical cable adaptors:** FC/PC socket on both sides
- || **Fibreglass rod** as insertion tool for fibre optic cables in empty tubes



Type	SO OA 5	SO OA 10	SO OA 15	SO FC/PC BC
Description	Opt. Attenuator 5 dB	Opt. Attenuator 10 dB	Opt. Attenuator 15 dB	Adapter FC/PC – FC/PC
Item No.	57001833	57001834	57001835	57001832

Type	SO EZH	SO NT Fibre LNB	NT 20-1200
Description	Fibreglass rod (insertion tool)	12 V PSU for Fibre LNB 40mm	Power plug for SO Quad /Quattro MK3
Item No.	57001836	57002374	57002140

OPTICAL COMPACT TRANSMITTER

- || Suitable for Wideband signals (57003502)
- || 2 wavelengths on one fibre (57003502)
- || High output power - high split ratio (up to 32)
- || Intended for use with OR 25 / OR 10 T



Type		OCH 25-31-33-0	OCH 25-55-00-0
Item No.		57003502	57003952
Wavelength	nm	1310 / 1330	1550
Optical Output power	dBm	each 9 / wavelength	each 9 / wavelength
Input level range	dBμV	75...90	75...90
Insertion loss	dBm	0...15	0...15
Frequency range	MHz	5 ... 2400	5 ... 2400
Power supply		230 V AC / 50 Hz / 6 W	230 V AC / 50 Hz / 6 W
Dimensions	mm	225 x 180 x 85	225 x 180 x 85
Weight	kg	2	2