

ACCESSOIRES

Wideband - Quattro Adapter

- || For conversion of a wideband LNB (L.O. 10,41 GHz) to conventional Quattro inputs
- || Extension of existing installations from one into two satellite positions without new wiring
- || Compact version
- || Remote powered from Quattro Inputs



Type		WQA 24
Item No.		57003355
Inputs		2
Input frequency	MHz	290...2340
Outputs		4
Output frequency	MHz	950...2150
Conversion gain	dB	0
Input power	dBμV	54...84
Isolation	dB	26
Power consumption	mA	150 @ 20 V
Input voltage	VDC	10...20
Dimensions	mm	90 x 80 x 40

Wideband Multi Splitter / Taps

- || WBS splits the signal equally on both outputs
- || WBT distributes a part of the signal to the outputs and attenuates the signal less than a splitter
- || Low insertion loss
- || DC power pass on all outputs



Type		WBS 2424	WBT 2424
Item No.		57003450	57003451
Frequency range SAT	MHz	290...2340	290...2340
Frequency range TER	MHz	5...862	5...862
Insertion loss	dB	5 (SAT) 4 (TER)	11 (SAT) 13 (TER)
Through loss	dB	2 (SAT) 2 (TER)	
Tap loss	dB		13
Return loss	dB	12	12
Dimensions	mm	129 x 129 x 51	129 x 129 x 51