




CABLE SIMULATOR PADS

- For LHD / NVD amplifier
- Frequency range 47-1218 MHz
- 5.6 mm thick

| Type | CSP 12045 | CSP 12060 | CSP 12075 | CSP 12090 | CSP 12105 | CSP 12180 |
|---------------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Item No. | 57003641 (PU 10) | 57003642 (PU 10) | 57003643 (PU 10) | 57003644 (PU 10) | 57003645 (PU 10) | 57004446 (PU 10) |
| EQ values db | 4.5 | 6.0 | 7.5 | 9.0 | 10.5 | 18 |
| 47 - 1218 MHz db | 3.7 | 4.9 | 6.2 | 7.4 | 8.6 | 14.8 |
| 47 - 1000 MHz db | 3.2 | 4.3 | 5.4 | 6.4 | 7.5 | 12.8 |
| 47 - 870 MHz db | 2.9 | 3.9 | 4.8 | 5.8 | 6.8 | 11.6 |
| Tolerance eq-val. max. db | +/- 0.5 | | | | | |
| Flatness db | +/- 0.2 | | | | +/- 0.25 | |
| Insertion loss db | ≤ 1 | | | | | |
| Return loss db | ≥ 18 | | | | ≥ 17 | |
| Impedance Ω | 75 | | | | | |

Length 25.4 mm (1")

FITTINGS PG 11

| Type | PG11m-Ff | PG11m-IECf | PG11m-3,5/12f | PG11m 3,5/12f |
|----------------------|---|---|---|--|
| |  |  |  | |
| Item No. | 57001082 | 10161203 | 57001141 | 57001291 |
| Description | PG 11 - Adapter PG 11 / F-female | PG 11 - Adapter PG 11 / IEC-female | PG 11 - Adapter PG 11 / 3.5 / 12 female | PG 11 - Adapter PG 11 / 3.5 / 12 female |
| Connector Pin length | 47 mm | 17 mm | 47 mm | 17 mm |

| Type | PG 11m-5/8f | PG 11 PC |
|-------------|---|---|
| |  |  |
| Item No. | 10161204 | 10161205 |
| Description | PG 11 - Reduction ring PG 11 / 5 / 8" | PG 11 Blind cap |