

## TWIN-WALL OUTLET SAT-IF

- Twin-wall outlet for 2-wire-SAT-IF application
- With DC pass
- Including cover plate and frame



Type	Frequency range	STD 2400
Item No.		10161174
<b>Description</b>		<b>Terminal-twin wall outlet</b>
<b>Attenuation</b>		
TV OUT (IEC-male)	dB	85-862 MHz
RF OUT (IEC-female)	dB	87.5-862 MHz
2x SAT OUT (F-female)	dB	950-2200 MHz
DC pass		12 V = max. 500 mA (over SAT-IF-connectors)

## ACCESSOIRES FOR ANTENNA WALL OUTLETS

Type	AD 3 SET	AD 3-2	AP 1
Item No.	57001452	57004041	10161348
Description	Set with cover plate (2 parts) and frame for 3-hole outlets (pure white)	cover plate 2 part for 3-hole outlets (pure white)	Frame (pure white)
Dimensions	mm 76 x 76 x 8 / 76 x 76 x 32	76 x 76 x 8	76 x 76 x 32

Type	R 75	R 75 DC
Item No.	57000813	57000990
Description	Terminal resistor	Terminal resistor DC isolated
Frequency range	MHz 0 – 2200	10 – 2200
Load	75 Ohm	75 Ohm
Application	For DC isolated walloutlets	For SAT-wall outlets with DC pass