

OCH2-1E / -2E OPTISCHER SENDER

- Optical multiple transmitter with 2 or 3 wavelengths
- High optical output level
- For optical distribution ratios until 1:128
- Optimized for wideband satellite signal input
- Integrated amplifier
- LTE filter at terrestrial input



Typ	OCH2-1E-31	OCH2-1E-55	OCH2-2E
Item No.	57004579	57004527	57004269
SAT-Inputs BK/Wideband LNB suitable	1x SAT F-Typ		2x SAT F-Typ
Frequency range	MHz 50-2340		
Min. input level	dBμV 65		
Max. output level	dBμV 85		
DC remote supply	V/mA 18 V / max. 400 mA		
Optical inputs	1 (SC / APC)		
Optical power	dBm ≥ 9	dBm ≥ 9	dBm ≥ 9 pro Wellenlänge
Output wavelength	nm 1310	nm 1550	nm 1310 und 1330
General			
DC input	18 - 20 V / min. 1,0 A (F-Typ) je nach Fernspeisung		
Power consumption	W 5 W (zzgl. Fernspeisung max. 30 W)	W 6 W (zzgl. Fernspeisung max. 30 W)	
Environmental temperature range	°C -10...+50 (nur für Innenmontage)		
Dimensions	mm 221 x 141 x 50		
Weight	g 800		

Suitable power supply NT 20-1.2 F Item-No. 57004430 or NT 20-3.3 F Item-No. 57003401